



Republic of the Philippines
Office of the President

PHILIPPINE SPORTS COMMISSION

REQUEST FOR QUOTATION

The Philippine Sports Commission, through its Bids & Awards Committee, invites interested **PHILGEPS-accredited** suppliers to submit SEALED signed formal quotation/s for:

Particular	Description					ABC (PHP)	Place of Delivery
Supply, Delivery and Installation of Wallmount Cabinet and Internet Services for Dormitories and MSAS Building at Philsports Complex	<u>Description</u>	<u>Qty</u>	<u>Unit</u>	<u>Unit Cost</u>	<u>Total Cost</u>	945,717.00	Property and Supplies Office, Philsport Complex (Formerly Ultra), Meralco Ave, Pasig City
	<p>1 GIGABIT CLOUD MANAGED SWITCHES >Hardware Specification: FIXED PORTS: 24 10/100/1000 Base-T ports (802.3 af/at compliant, 4 SFP 1000Base-X ports, 370W PoE power >SWITCHING CAPACITY: 336Gbps >PACKET FORWARDING RATE: 42Mpps MAC >ADDRESS: Support static MAC address, MAC address filtering >MAC ADDRESS TABLE SIZE: 8K >NUMBER OF VLANS: 4094 >LINK AGGREGATION: Supported >PORT MIRRORING: Many-to-one mirroring >SPANNING TREE: STP, RSTP LLDP: Support ACL: IP standard ACL MAC extended ACL, IP extended ACL, Port ACL for Layer 2 ports (physical port/AP) QoS: Port-based speed limit (ingress/egress) >SECURITY: Port protection >MANAGEMENT: Web management >DHCP:DHCP snooping EEE: Support >Physical specifications: DIMENSIONS: 440X293X44mm 24 BASE-T PORTS: (support PoE and PoE+) MAXIMUM PoE/PoE+ OUTPUT POWER PER SWITCH: 370W MAXIMUM OUTPUT POWER: 30W TEMPERATURE: OPERATING TEMPERATURE: 0 °C ~ 50 °C STORAGE TEMPERATURE: minus 40 °C ~ 70 °C HUMIDITY: OPERATING HUMIDITY 10% ~ 90% RH STORAGE HUMIDITY 5% ~ 90% RH</p>	15	units	20,307.00	304,605.00		
<p>2 4RU Wall Mounted Cabinet >Bolted-type Data Cabinet w600mm d450mm h250mm >Powder Coated Black >EIA-310-D: Standard 19" rack opening system >Collapsible frame and panels ***more on the next page*** >Galvanized Iron Ga. #16, 2pcs adjustable</p>	15	Units	7,302.00	109,530.00			

	<p>square-holed L-type mounting rail >with 1 unit exhaust fan and 3 cable entries (2"x4") with removable covers on top and bottom panel >Swing out detachable plexiglass front door with push lock and key >Detachable vented side panels with camlock and key >Fixed back panel >with 1 unit vertical PDU with 2 CO's. 220V AC, 2 meter electrical cord and 3 prong plug >with 1 unit vertical ring-type cable manager at the back >with 8 sets of cagenut and bolt >Powder Coated Black finish</p> <p>3 UPS 650VA with Built-in AVR Boost & Buck 15 Units 2,200.00 33,000.00</p> <p>>for Voltage Stabilization >LED display for ease of monitoring >Excellent microprocessor-based digital control guarantees high reliability >Wide input voltage range >Short circuit, battery overcharge, discharge, overload & surge protections >Resettable Circuit Breaker</p> <p>4 WIRELESS ACCESS POINT 54 Units 9,233.00 498,582.00</p> <p>>Hardware specifications: RADIO: Dual-radio dual-band, Radio 1:2.4G 11 ax/5G 11ax: 2x2 MIMO; Radio 2: 5G 11ax:2x2 MIMO PROTOCOL: supports standards 802.11ax, dual-radio, dual-band, concurrent 802.11ax and 802.11a/b/g/n/ac OPERATING BANDS: 802.11b/g/n/ax:2.4G~2.483GHz 802.11a/n/ac/ax:5. 150~5.350GHz, 5.47~5.725GHz, 5.725~5.850GH Up to 4: 2x2:2 in 2.4GHz,2x2:2 in GHz >MAXIMUM THROUGHPUT: (5G+5G mode) per AP:2.4Gbps Radio 1: 5G low band 1.2Gbps; Radio: 5G high band 1.2Gbps 2.4G+5G operation mode, maximum throughput per AP:1.775Gbps Radio1: 2.4G 0.574Gbps Radio2:5G 1.2Gbps >ANTENNA: Integrated antenna design ANTENNA GAIN: 2.4G:3dBi, 5G:3dBi >SERVICE PORTS: 1 10/100/1000M Ethernet ports, PoE In >MANAGEMENT PORT: 1 console port >RESET BUTTON: Supported >ANTI-THEFT LOCK: Supported >LED INDICATOR: 1 LED indicator (Support red, green, blue, orange and flashing mode, which indicates device access) >TRANSMIT POWER: ≤100mw (20dBm) (vary depending on different countries) >ADJUSTABLE POWER: 1dBm >POWER SUPPLY: LOCAL POWER SUPPLY: (DC48V/1A), PoE (802.3af)-full spectrum operation >POWER CONSUMPTION: ≤12.95W Physical Specification: Operating Temperature: -10°C to 50°C >STORAGE TEMPERATURE: minus 40 °C to 70 °C ***more on the next page*** >HUMIDITY: Operating Humidity: 5% to 95% (non-condensing)</p>		
--	---	--	--

	<p>>STORAGE HUMIDITY: 5% to 95% (non-condensing) >INSTALLATION MODE: Ceiling/wall-mountable >DIMENSIONS: (WxDxH): 153mm x 193mm x 22mm >WEIGHT: ≤0.5kg (include mount kit) >IP RATING: IP41 250,000 HOURS >Software Specification: MAXIMUM CLIENTS: 1024 >BSSID CAPACITY: Up to 32 REMOTE INTELLIGENT PERCEPTION TECHNOLOGY >Supported STA CONTROL: SSID/radio-based >BANDWIDTH CONTROL: STA/SSID/AP-based bandwidth control >DATA ENCRYPTION: WPA(TKIP), WPA-PSK, WPA2(AES), WPA3, WEP (64/128 bits) IP: IPv4 and IPv6 address Multicast routing: Multicast to unicast conversation >DHCP service: DHCP Snooping Option 82, Server, Client >MANAGEMENT AND MAINTENANCE: SNMP: SNMPV1, V2cV3 LLDP:LLDP, LLDP-MED, LLDP-POE Syslog/Debug: Support FAT/FIT/ MACC mode switching: Factory default firmware supports fat (stand alone) or FIT mode (WS controller) or MACC mode management ***nothing follows***</p> <p>Delivery Terms: Twenty (20) Calendar Days</p>		
--	--	--	--

The following documents must be submitted from 02 May 2022 to 05 May 2022 at 5:00 pm, directly to the Bids and Awards Committee Secretariat located at Room 207, 2nd Floor, Administration Building, Rizal Memorial Sports Complex, Pablo Ocampo Sr. St. Malate Manila.

1. PHILGEPS Registration or PHILGEPS Certificate
2. Updated Omnibus Sworn Statement (notarized), per GPPB Resolution 16-2020
3. 2022 Mayor's/Business permit
4. Updated Tax Clearance or ITR Form 2021

For additional information, please contact the Procurement Office nos. Telefax: 524-3512 or 524-4408 loc. 153/147.

Quotations must be properly labeled with reference number on the project offered. In case the deadline falls on non-working, legal holiday, or special non-working holiday, the deadline shall be on the next working day.

The Commission reserves the right to not accept any and all quotations or not award the contract on the following grounds:

- There is prima facie evidence of collusion;
- The BAC failed to follow prescribed procurement procedures; and or
- There are justifiable grounds where the contract will not redound to the benefit of the government without incurring any liability to the affected bidder/s.

ATTY. GUILLERMO B. IROY, JR.
BAC Chairman

Date Posted on PHILGEPS & PSC website: May 2, 2022